AUTHOR INDEX

Abdul, M. A., 193 Andres, M. V., 417 Angell, J. B., 427 Armand, M., 1

Baltes, H. P., 325 Barth, P. P., 427 Bayle, C., 399 Bouwstra, S., 153 Brett, M. J., 325

Canqian Yang, 51 Cauhapé, J. S., 399 Chavanne, D., 193 Coccoli, G., 235 Collings, M. S., 359

Daniels, P. B., 11 Deacon, J. K., 11

Eddowes, M. J., 11 El Yamani, H., 193 Evans, A. G. R., 257 Ewen, R. J., 359

Fabry, P., 1, 33 Foulds, K. W. H., 417 Fraser, D. E., 325 Fray, D. J., 185 French, P. J., 119, 257 Frindt, R. F., 105

Gabriel, K. J., 95 Gayet, H., 387 Giuliani, J. F., 25 Groppelli, S., 235 Gros, J. P., 33

Hill, C. A. S., 359 Ho, M. H., 445 Honeybourne, C. L., 359 Huijsing, J. H., 119, 135 Hykaway, N., 105

Jin, H., 337

Karube, I., 199, 435 Kemmer, J. A., 169 Kimura, J., 435 Kinjo, N., 375 Kleitz, M., 33 Kumar, R. V., 185 Kümmel, M., 51 Kuriyama, T., 435

Lam, L. K. C., 337 Lantto, V., 347 Leppävuori, S., 347 Lian, W. J., 119 Lucat, C., 399 Lukosz, W., 273, 285

Mari, C. M., 19
Meierhöfer, I., 211
Ménil, F., 399
Middelhoek, S., 119
Million-Brodaz, J. F., 33
Mohan, S., 297
Montero-Ocampo, C., 1
Moritz, W., 211
Morrison, S. Roy, 105
Müller, L., 211
Muller, R. S., 63
Murakami, T., 435

Nagai, M., 145 Nani, G., 243 Nellen, Ph. M., 285 Nishino, T., 145

Ohara, S., 375

Parameswaran, M., 325 Pedley, D. G., 11 Portier, J., 399 Posch, H. E., 77

Rajanna, K., 297 Robinson, A. M., 325 Romppainen, P., 347

Saeki, T., 145 Sberveglieri, G., 235 Sears, W. M., 105 Seifert, M., 309 Senturia, S. D., 221 Silard, A. P., 243 Smith, R. L., 221 Søeberg, H., 51 Spohn, P. K., 309 Sugawara, T., 375

Tamiya, E., 199
Terzaghi, G., 19
Tiefenthaler, K., 273, 285
Tran-Minh, C., 193
Trimmer, W. S. N., 95
Tsuchitani, S., 375
Tsunoda, T., 375
Tudor, M. J., 417

van de Pol, F. C. M., 153 van Lintel, H. T. G., 153 van Oudheusden, B. W., 135

Walker, J. A., 95 Wolfbeis, O. S., 77

Yee, S., 337 Yu, L. T., 387 Yu-Chong Tai, 63

Zdeblick, M. J., 427 Zhang Weixin, 85 Zhao Yibing, 85

SUBJECT INDEX

Amperometric measurement integrated multibiosensor for simultaneous and potentiometric measurement, 435

Amplifier microminiature fluidic, 427 Automated system for pesticide detection, 193

Biochemical sensor(s)
integrated optical input grating
couplers as, 285
sensitivity of integrated optical grating

and prism couplers as, 273 Biosensor(s)

integrated multi-, for simultaneous amperometric and potentiometric measurement, 435

micro-, for clinical analyses, 199 potentiometric, based on immobilized enzyme membrane and fluoride detection, 445

Bismuth molybdate evaporated films, gas-sensing properties of, 105

Calcium

semiconductor oxides $Sr_{1-y}Ca_yFe_{3-x}$ ($0 \le y \le 1$; $0.19 \le x \le 0.50$), role of mineral binder in sensing properties of screen-printed layers of, 399

Carbon monoxide gas sensor comprising porous hydroxyapatite ceramics, new type, 145

Carbon monoxide/carbon dioxide gas mixtures, determination of composition of; solid-state O meter equipped with CeO_{2-x} thick-film electrode, 19

Chemical sensors

(bio), sensitivity of integrated optical grating and prism couplers as, 273

Chemical vapor microsensors integrated optical, 25

Cerium

solid-state O meter equipped with CeO_{2-x} thick-film electrode;

determination of composition of CO/CO₂ gas mixtures, 19

Clinical analyses micro-biosensors for, 199

CMOS technology capacitive humidity sensor based on, with adsorbing film, 325

Digital or frequency output sensors with, 119

Electrode(s)

CeO_{2-x} thick-film, solid-state O meter equipped with; determination of composition of CO/CO₂ gas mixtures, 19

miniature liquid junction reference, with micromachined Si cavity, 337 solid-state Na⁺-selective, ionic conductor for, NASICON, 33

Electrolyte

polymer, as internal ionic bridge for ion solid-state sensors, 1

Energy signals

bifacial, large-area Si sensors for radiative, 243

Enzyme membrane potentiometric biosensor based on immobilized, and fluoride detection, 445

Flow friction sensor integrated, 135

Flow meter

lightly-doped polysilicon bridge as, 63 self-heated thermistor, for small liquid flow in microchannels, 51

Fluorescence quenching optical sensors; fibre-optic humidity sensor based on, 77

Fluoride detection potentiometric biosensor based on immobilized enzyme membrane and, 445

Fluoride-sensitive membrane for ISFETs, 211

Frequency output sensors with digital or, 119 Si pressure sensor, sensitivity and mode spectrum of, 417

Gas captors

application of linear potential sweep voltammetry (LPSV) to make; conditions of detection of unsaturated hydrocarbons, 387

Gas detection

toxic, thin films of conjugated macrocyclic ligands for, 359

Gas mixtures

 CO/CO_2 , determination of composition of; solid-state O meter equipped with CeO_{2-x} thick-film electrode, 19

Gas-sensing properties

of Bi molybdate evaporated films, 105 Gas sensor(s)

CO₂, comprising porous hydroxyapatite ceramics, 145

NO₂, radio frequency magnetron sputtering growth and characterization of In-Sn oxide (ITO) thin films for, 235

response studies of some semiconductor, under different experimental conditions, 347

Grating couplers

integrated optical input, as biochemical sensors, 285

interaction of aqueous solutions with, used as integrated optical sensors and their pH behaviour, 309

sensitivity of integrated optical, and prism couplers as (bio)chemical sensors, 273

Humidity sensor(s)

capacitive, based on CMOS technology with adsorbing film, 325

fibre-optic, based on fluorescence quenching, 77

using ionic copolymer and its application to humidity-temperature sensor module, 375

Hydrogen sensors

development of solid-state, 185

Hydrogen sulphide

temperature characteristics of H₂Ssensitive Pd-gate MOS transistor, 85

Hydroxyapatite ceramics

new type of CO₂ gas sensor comprising porous, 145

Immunosensing

surface plasmon resonance applied to,

Indium

-tin oxide (ITO) thin films for NO₂ gas sensors, radio frequency magnetron sputtering growth and characterization of, 235

Ion solid-state sensors

polymer electrolyte as internal ionic bridge for, 1

Ionic bridge

polymer electrolyte as internal, for ion solid-state sensors, 1

Ionic conductor

for solid-state Na⁺-selective electrode, NASICON, 33

Ionic copolymer

humidity sensor using, and its application to humidity-temperature sensor module, 375

Iron

semiconductor oxides $Sr_{1-y}Ca_yFe_{3-x}$ (0 $\leq y \leq 1$; 0.19 $\leq x \leq$ 0.50), role of mineral binder in sensing properties of screen-printed layers of, 399

ISFETs

fluoride-sensitive membrane for, 211

Linear potential sweep voltammetry application of LPSV to make gas captors; conditions of detection of unsaturated hydrocarbons, 387

Liquid flow

in microchannels, self-heated thermistor flowmeter for small, 51

Liquid junction reference electrode with micromachined Si cavity, miniature, 337

Macrocyclic ligands

thin films of conjugated, for toxic gas detection, 359

Meandering path thin-film strain gauge studies on, 297

Micro-biosensors

for clinical analyses, 199

Microminiature fluidic amplifier, 427

Micropump

piezoelectric, based on micromachining of Si, 153

Micro rotary actuator

using shape memory alloys, 95

Microsensor(s)

integrated optical chemical vapor, 25

packaging and system partitioning, 221 Mineral binder

role of, in sensing properties of screenprinted layers of semiconductor oxides $Sr_{1-y}Ca_yFeO_{3-x}$ (0 $\leq y \leq$ 1; 0.19 $\leq x \leq$ 0.50), 399

MOS transistor

temperature characteristics of H₂S-sensitive Pd-gate, 85

Multibiosensor

integrated, for simultaneous amperometric and potentiometric measurement, 435

NASICON

ionic conductor for solid-state Na⁺selective electrode, 33

Nitrogen dioxide

gas sensors, radio frequency magnetron sputtering growth and characterization of In-Sn oxide (ITO) thin films for, 235

Nuclear radiation Si detectors for, 169

Optical chemical vapor microsensors integrated, 25

Optical input grating couplers integrated, as biochemical sensors, 285 Optical sensor(s)

fibre-optic humidity sensor based on fluorescence quenching, 77

interaction of aqueous solutions with grating couplers used as, and their pH behaviour, 309

Oxygen meter

solid-state, equipped with CeO_{2-x} thick-film electrode; determination of composition of CO/CO₂ gas mixtures, 19

Palladium

temperature characteristics of H₂Ssensitive Pd-gate MOS transistor, 85

Pesticide detection automated system for, 193

pH behaviour

interaction of aqueous solutions with grating couplers used as integrated optical sensors and their, 309

Piezoelectric micropump

based on micromachining of Si, 153

Piezoresistance

polysilicon strain sensors using shear, 257 Plasmon resonance

surface, applied to immunosensing, 11

Polymer electrolyte

as internal ionic bridge for ion solidstate sensors, 1

Polysilicon bridge

lightly-doped, as flow meter, 63

Polysilicon strain sensors

using shear piezoresistance, 257

Potentiometric biosensor

based on immobilized enzyme membrane and fluoride detection, 445

Potentiometric measurement integrated multibiosensor for simultaneous amperometric and, 435

Pressure sensor

Si, sensitivity and mode spectrum of frequency-output, 417

Prism couplers

sensitivity of integrated optical grating and, as (bio)chemical sensors, 273

Radiative energy signals

bifacial, large-area Si sensors for, 243

Response studies

of some semiconductor gas sensors under different experimental conditions, 347

Semiconductor gas sensors

response studies of, under different experimental conditions, 347

Semiconductor oxides

 $Sr_{1-y}Ca_yFeO_{3-x}$ (0 $\leq y \leq 1$; 0.19 $\leq x \leq 0.50$), role of mineral binder in sensing properties of screen-printed layers of, 399

Sensing properties

of screen-printed layers of semiconductor oxides $Sr_{1-y}Ca_yFeO_{3-x}$ (0 $\leq y \leq 1$; 0.19 $\leq x \leq$ 0.50), role of mineral binder in, 399

Shape memory alloys

micro rotary actuator using, 95

Silicon

miniature liquid junction reference electrode with micromachined Si cavity, 337

piezoelectric micropump based on micromachining of, 153

polysilicon strain sensors using shear piezoresistance, 257

Silicon detectors

for nuclear radiation, 169

Silicon pressure sensor

sensitivity and mode spectrum of frequency-output, 417

Silicon sensors

for radiative energy signals, bifacial large-area, 243

Sodium

NASICON, ionic conductor for solidstate Na⁺-selective electrode, 33

Solid-state hydrogen sensors development of, 185

Solid-state Na⁺-selective electrode ionic conductor for, NASICON, 33

Solid-state oxygen meter

equipped with CeO_{2-x} thick-film electrode; determination of composition of CO/CO_2 gas mixtures, 19

Solid-state sensors

ion, polymer electrolyte as internal ionic bridge for, 1

Sputtering growth

radio frequency magnetron, and characterization of In-Sn oxide (ITO) thin films for NO₂ gas sensors, 235

Strain gauge

studies on meandering path thin-film, 297

Strain sensors

polysilicon, using shear piezoresistance, 257

Strontium

seniconductor oxides $Sr_{1-y}Ca_y$ - FeO_{3-x} ($0 \le y \le 1$; $0.19 \le x \le 0.50$), role of mineral binder in sensing properties of screen-printed layers of, 399

Surface plasmon resonance applied to immunosensing, 11

System partitioning microsensor packaging and, 221

Temperature

humidity—, sensor module, humidity sensor using ionic copolymer and its application to, 375

Temperature characteristics of H₂S-sensitive Pd-gate MOS transistor, 85

Tin oxide

In-, (ITO) thin films for NO₂ gas sensors, radio frequency magnetron sputtering growth and characterization of, 235

Toxic gas detection

thin films of conjugated macrocyclic ligands for, 359

Unsaturated hydrocarbons

conditions of detection of; application of linear potential sweep voltammetry (LPSV) to make gas captors, 387

